



www.hidenanalytical.com

info@hiden.co.uk

Hiden QIC BioStream

For fermentation off-gas analysis



www.HidenAnalytical.com



info@hiden.co.uk

Introduction

- This presentation provides an overview of gas analysis systems for fermentation off gas analysis.
- Fermentation off gas analysis by mass spectrometry provides real time trend analysis of the gases and vapour species that are important to product yield, O₂ CO₂ H₂ CH₄ for example, and provides vital data for real time process monitoring.
- The mass spectrometer is user programmable to analyse a broad range of gas and vapour species and covers most species of interest in both aerobic and anaerobic applications.
- The QIC series gas analysers manufactured by Hiden Analytical include systems configured to address the application of fermentation off gas analysis.


Hiden QIC Series Gas Analysis Systems

- The QIC series gas analysers are mass spectrometers configured for real time gas analysis, fermentation off gas for example.
- The QIC systems provide for multiple species real time trend analysis providing quantitative gas analysis.
- The QIC systems include an inert silica capillary with fast response to both gases and vapours.



QGA A single stream real time gas analyser




QIC Inlet Technology



- Quartz and Platinum Wetted Surfaces → No memory effects
- Heated Capillary → No condensation effects
- Flow Matched → Optimum response / recovery
- Minimal Internal Volume → PPB detection


**These features provide excellent analyser performance for
fermentation off-gas analysis**

QIC Inlet- MS Interface Overview

**Key**

- G1 Penning gauge
- VR1 QIC Inlet bypass control valve
- P1 60 l/s turbo drag pump
- P2 Backing and bypass Scroll pump
- MS UHV Housing (Mass spectrometer chamber)

Fast Response to Permanent Gases / Vapours



Data shows the response of the QIC inlet to gas and vapour during switching between a dry He stream and a wet H₂ and Ar flow. For clarity, only the H₂ and H₂O data is shown in the graph.

QIC BioStream

Modular multi-stream off-gas analyser, bench top or cart configured for analysis of:

8, 20, 40 or 80 sample streams

for:

- high flow ~ up to 12 l/min sample flow

Or

- 20, 40 or 80 sample streams

for:

- low flow small volume reactors – 4 ml/min sample flow



For flow rates up to 12 l/minute the QIC BioStream can measure selected stream flow rate.
For higher flow rates, sample flow is connected to the QIC BioStream via a T piece.

QIC BioStream-C bench top system

Modular configuration:

Small footprint instrument:
535mm deep X 530mm wide

20 stream version shown
with dual mass flow meters for
accurate selected flow
measurement in the
flow range to 12 l/min.




QIC BioStream-C bench top system


Small footprint instrument:
535mm deep X 530mm wide

Top mounted Proteus Valve
20, or 40 stream versions.


20 stream version shown
with dual mass flow meters for
accurate selected flow
measurement in the flow range to
12 l/min.

Flow measurement is
for the O₂ uptake (OUR)
and CO₂ expiration rate (CER)
calculations.






QIC BioStream switching time between sample streams in > 0.6 seconds




Hiden Proteus Multistream Valve	
Type	Gas Selector valve - relies on novel face sealing technology to provide effective sealing with long life.
Max Operating Temperature	120°C
Minimum Sample Flow	Not applicable - Determined by analyser (no sample lost)
'Crosstalk' from other samples	Zero
Number of operations before maintenance	>6 x 106
Memory (carry over) From previous sample	Class leading low memory due to minimised internal switching volume and low sample wetted surface area. The face seal is isolated from the sample by a secondary internal seal.
Number of ports	20, 40, 80
Actuation	Direct drive, high torque microstepping motor with IP65 protected incremental rotary encoder providing home z-position and closed loop motion control. Full motion management including intelligent acceleration/deceleration, position maintenance, bi-directional drive and position error annunciation.

Positioning accuracy	+/- 0,09°
Full brown-out sensing and protection	Yes
Communication (valve port position select)	Binary, BCD RS232C
Available as separate product	Yes




Triple Filter Quadrupole Mass Spectrometer

- Precision machined ceramic supports
- Independently driven RF pre and post filters
- Long term stable operation



- Oxygen , Nitrogen and Argon measured over 110 hours
- Data shows stability of the Argon signal for an extended period

QGA 2 Software for Quantitative Gas Analysis




An application specific software package for quantitative gas and vapour analysis providing real time continuous analysis of up to 32 species with concentrations measured in the range 5PPB to 100%

- Automatic subtraction of spectral overlaps
- Automated calibration routines
- Mass spectral library with intelligent scan feature
- Multi-stream support




Multiple stream sequence set up - 80 stream example



Click to add
or subtract
a stream
from the
analysis sequence

Fermenters can be added or subtracted from the stream sequence at any time during the analysis with a simple click on the stream LED.


Multi stream gas analysis - The real time trend analysis of up to 4 selected streams can be viewed in real time and in review



Data Export

- Data export to MS Excel.
- New workbook for each data file.
- Quantitative data, raw data values and corrected data values are exported.
- Calibration factors and background correction values are recorded.
- The workbook contains a worksheet for each gas stream.

Data for up to 80 gas sample streams



Gas composition

Time (ms)	Nitrogen 28	Argon 40	Oxygen 32	Water 18
6	5.64E+03	1.27E-07	1.46E-09	2.67E-08
7	5.64E+03	1.01E-07	1.09E-09	1.06E-08
8	5.64E+03	1.02E-07	1.08E-09	1.07E-08
9	5.64E+03	1.03E-07	1.07E-09	1.08E-08
10	5.64E+03	1.04E-07	1.06E-09	1.09E-08
11	1.22E+02	8.02E-08	1.00E-09	1.04E-08

RAW data

Time (ms)	Nitrogen 28	Argon 40	Oxygen 32	Water 18
6	5.64E+03	1.27E-07	1.46E-09	2.67E-08
7	5.64E+03	1.01E-07	1.09E-09	1.06E-08
8	5.64E+03	1.02E-07	1.08E-09	1.07E-08
9	5.64E+03	1.03E-07	1.07E-09	1.08E-08
10	5.64E+03	1.04E-07	1.06E-09	1.09E-08
11	1.22E+02	8.02E-08	1.00E-09	1.04E-08

Corrected data

Time (ms)	Nitrogen 28	Argon 40	Oxygen 32	Water 18
6	5.64E+03	1.27E-07	1.46E-09	2.67E-08
7	5.64E+03	1.01E-07	1.09E-09	1.06E-08
8	5.64E+03	1.02E-07	1.08E-09	1.07E-08
9	5.64E+03	1.03E-07	1.07E-09	1.08E-08
10	5.64E+03	1.04E-07	1.06E-09	1.09E-08
11	1.22E+02	8.02E-08	1.00E-09	1.04E-08

Calibration factor

Background	Calibration Factor
8.19E-11	1.01349
1.50E-10	0.91654
1.54E-10	0.9474
1.14E-09	0.95104
0	1
0	1
0	1
0	1

Stream 1

Stream 1	Stream 3	Stream 4	Stream 5	Stream 7	
38	903940	80.193	1.009	18.102	0.695
39	932948	80.203	1.016	18.076	0.705
40	961778	80.065	1.018	18.221	0.696
41	990701	80.181	1.015	18.091	0.714
42	1019570	80.185	1.031	18.077	0.707
43	1048680	80.149	1.023	18.125	0.704
44	1077430	80.12	1.023	18.155	0.702
45	1106301	80.076	1.013	18.218	0.693
46	1135051	80.207	0.996	18.099	0.698
47	1163923	80.185	1.018	18.089	0.708
48	1192796	80.148	0.997	18.172	0.684
49	1221007	80.195	1.011	18.1	0.694

Ready

OPC - Data Output

The screen shot is from an OPC data viewer showing data tags for each stream and for each gas channel.

RQ/CER/OUR data can be output for each stream

OPC data can be selected as raw, corrected or %,PPM values

The screenshot shows the MatrikonOPC Explorer interface with the title bar "MatrikonOPC Explorer - [Untitled]" and a menu bar with File, Server, Group, Item, View, Help. The left pane displays a tree view of network resources, including "localhost \PC10", "Matrikon.OPC.Simulation.1", "National Instruments.Variable Engine.1", and "Network Neighborhood". A tooltip box highlights the text "Tags are automatically updated for the active streams: \\\QGAPro\2_2 is the current value for stream 2 gas 2. \\\QGAPro\2_RQ is the current RQ value for stream 2." The right pane shows a table titled "Contents of '1'" with columns: Item ID, Access Path, Value, Quality, Timestamp, and Status. The table lists numerous tags for streams 2 and 3, such as "\\\QGAPro\2_1" through "\\\QGAPro\2_16", "\\\QGAPro\2_2" (Value: 18.7962157343888), "\\\QGAPro\2_3" (Value: 0.8728409069347), "\\\QGAPro\2_4" (Value: 4557.52377693532), "\\\QGAPro\2_5" (Value: 1.21783751262622), "\\\QGAPro\2_6" (Value: 0), "\\\QGAPro\2_7" (Value: 0), "\\\QGAPro\2_8" (Value: 0), "\\\QGAPro\2_9" (Value: 0), "\\\QGAPro\2_CER" (Value: 0.00121341998855826), "\\\QGAPro\2_OUR" (Value: 0.001848416579476), "\\\QGAPro\2_RQ" (Value: 0.656441451928897), "\\\QGAPro\3_1" (Value: 79.3545815798548), "\\\QGAPro\3_10" (Value: 0), "\\\QGAPro\3_11" (Value: 0), "\\\QGAPro\3_12" (Value: 0), "\\\QGAPro\3_13" (Value: 0), "\\\QGAPro\3_14" (Value: 0), "\\\QGAPro\3_15" (Value: 0), "\\\QGAPro\3_16" (Value: 0), "\\\QGAPro\3_2" (Value: 1.51106640662871), "\\\QGAPro\3_3" (Value: 18.437938745529), "\\\QGAPro\3_4" (Value: 0.696413267987495), and "\\\QGAPro\3_5" (Value: 0). All tags are marked as "Good, non-specific" and "Active".

Tags are automatically updated for the active streams:
\\\QGAPro\2_2 is the current value for stream 2 gas 2.
\\\QGAPro\2_RQ is the current RQ value for stream 2.

Real-time data export, system control and I/O for process control

Three options for output of real time data

- OPC for process control providing real time data tags from QGA Pro software.
- RS232 streamed data in ascii format from the mass spectrometer interface unit.
- Socket interface for windows client compatible applications with MASsoft Pro software.

System control and outputs

- 5 I/O for TTL signal control for automatic operation- start /stop for example.
- Up to 16 channel signal output options -0-10V analogue outputs.

System data logging

- Three RS485 inputs provide for up to three device type protocols for reading data from external devices, temperature for example. Synchronously logged and displayed with the mass spectrometer data.
- Up to 16 channel signal output options as 0-10V analogue.



QIC BioStream gas analyser for sampling fermentors with sample flow rates in the range of litres /min to 0.1 l/min

- Small diameter sample tubing is used to connect the QIC BioStream to the fermentors.
- Sample gas flow through the sample tubing is induced by creating a pressure gradient along the tube.
- The sample flow may be achieved by running the fermentor at a positive pressure & venting the sample flow to ambient pressure after analysis.
- Alternatively, a sampling pump may be connected to the analyzer exhaust.
- This type of system will typically accept individual sample flow rates from several litres/minute to 0.1 litres/minute. Sample transit times become unacceptably long (several minutes) below 0.02 litres/minute.
- Small fermentors and miniature reactors use the low flow configuration with flow rate < 4ml/minute.

QIC BioStream gas analyser for small fermentors with very low flow 4ml/min

- The QIC BioStream low flow system utilizes the unique capability of the Proteus multistream selector valve to operate under very low pressure (vacuum) conditions.
- This system is optimized for fast response with very low sample flow rates. This is achieved with small-bore capillary tubing. The sampling lines then become the 1st stage of the inlet pressure reduction system. The exhaust of the Proteus valve is connected to the dry scroll pump to provide a vacuum of a few mbars absolute within the valve.
- Atmospheric pressure sample gas enters the capillary sample tubing at the sampling point at 1.8 metres/sec (typical for 0.2mm ID x 2.0 metre sampling capillary) then accelerates rapidly along the tubing due to the progressive expansion of the sample.
- For example, 4 ml/minute atmospheric flow expands to $4 \times >200 = 800$ ml/min (0.8 litres/minute)
- This increase in sample volume flow rate provides rapid sample transit along the sampling capillary & the fast switching response, switching time between sample streams is < 0.6 seconds.

Connecting to fermentors with low flow

20, 40 or 80 way systems are available in low flow configuration.



Low flow 40 way Proteus multistream sampling valve Configuration. The Proteus multi stream valve is close coupled to the mass spectrometer vacuum for low flow.



Sampling lines for low flow sampling , female luer lock fittings, shown with disposable hydrophobic filters< operates with flow ~ 4ml/min.

Sample conditioning for the analyser

The QIC BioStream off gas analyser requires sample to be:

Non condensing.

A hydrophobic filter should be included in each sample line to avoid water droplets entering the analyser.

and without any foam or overspill.

For larger reactors a simple foam trap in the sample line avoids liquid entering the analyser.

For advice on how to connect fermenters to Hiden's QIC BioStream real time gas analyser- please send a schematic detailing your fermenter layout, flow rates, and gas/vapour species.

Summary - QIC BioStream for off-gas analysis

QIC BioStream – cart or compact bench top configuration

Off gas analysis for 8, 20, 40, or 80 streams


Analysis of gases and vapours

Triple filter quadrupole mass spectrometer

OUR/CER/RQ

Data output through OPC shared variable engine

Lifetime application and service support



QIC BioStream mobile cart



QIC BioStream-C bench top

- www.HidenAnalytical.com
- The Hiden website is an excellent resource with product pages, brochures, catalogues, product pages with some application notes, presentation and other information.
- Contact +44 1925 445225 for direct support.



www.HidenAnalytical.com



info@hiden.co.uk